

PACSystems* RSTi-EP CPE100

Programmable Automation Controller

The demand for improved asset performance and productivity is increasing in manufacturing and infrastructure markets. They require even smaller applications with robust execution performance and a range of connectivity options to real-time application status information and diagnostics.

Emerson has designed a small form factor, high performance controller that enables equipment builders to improve performance and flexibility of their machines while reducing size, complexity, and cost.

Small Footprint. Big Impact.

Leverage the power and flexibility of PACSystems in smaller applications. RSTi-EP CPUs make it possible to incorporate the entire PACSystems programming suite in stand-alone applications or as auxiliary control in larger process applications that use RX3i. This simplifies training for operators and maintenance workers and streamlines application development and integration.

CPE100 supports real-time application status, remote diagnostics and:

- Dual LAN interfaces with four Ethernet ports
- Built-in RS-232 serial port
- Support for a range of communications protocols, including PROFINET
- Up to 1 MB of non-volatile user memory All in just 1.5” (38.1mm) of DIN rail space.

Speaking the Same Language

With CPE100, you can use the same runtime as existing RX3i controllers and leverage existing application libraries and templates while scaling footprint and performance for smaller application installations. Fast, easy-to-configure PACSystems technology and an extensive range of I/O options support scalable automation and highly distributed modular machine designs.



PROFINET Advantage

PROFINET I/O solutions from GE can provide productivity and performance advantages for virtually any type of control application in a range of industries. PROFINET supports a variety of I/O without compromising system performance and can operate in high-noise environments. Connect to any of Emerson’s purpose-built I/O families through a PROFINET interface for advanced flexibility and performance.

Advanced Security

Without proper cybersecurity in place, industrial controls may be vulnerable to cyber threats. Emerson PACs enlist defense-in-depth architecture to help protect assets from these threats. The RSTi-EP CPE100 incorporates technologies such as Trusted Platform Modules and secure, trusted, and measured boot. Centralized configuration allows encrypted firmware updates to be executed from a secure central location. And, a suite of cybersecurity technology and tools help prevent unauthorized updates while built-in security protocols help protect against man-in-the-middle and denial of service attacks.

Feature	Feature Benefit
High performance	<ul style="list-style-type: none"> ■ Latest CPU features integrated System-on-Module processor for reduced latency and more precise data or I/O control ■ Full PACSystems library of programming capabilities helps enable quick and convenient application development
Simplification	<ul style="list-style-type: none"> ■ Store large amounts of data for better system statistics and analysis ■ Store application files right on the control for fast access to drawings, debug or startup information, operational notes, and more ■ Built-in multiport switch reduces I/O wiring cost and installation time ■ Three-port switch allows for I/O network redundancy via Media Redundancy Protocol and a connection for local HMI without extra networking equipment
Security	<ul style="list-style-type: none"> ■ Secure-by-design features include Trusted Platform Module and Measured Boot technology to enable encrypted, digitally signed firmware updates and help stop attempts to introduce malware onto the CPU. These same technologies are included on the PACSystems RX3i product line. ■ Achilles Level 2 certification indicates that it meets industry standards for reliability and communications robustness ■ Role-based access control assigns user privileges based on pre-defined levels of authorization, enhancing system security
PROFINET distributed I/O connectivity	<ul style="list-style-type: none"> ■ Open standard for high-speed I/O connectivity ■ Support for Media Redundancy Protocol for robust operation ■ Replace devices without the need to reconfigure them for improved uptime

Specifications

Part Number

- EPSCPE100

Form Factor

- Standalone

Storage

- 1MB

I/O

- 2k Bits Discrete I/O
- 32k Words for Analog I/O

Field Agent Support

- External

Redundancy Support

- Media Redundancy Protocol (MRP)

Ethernet Port

- 1 – 10/100
- 1 – 3-port switch 10/100

Ethernet Communications

- SRTP Client/Server – (Max 8 Connections)
- Modbus TCP/IP – (Max 8 Connections)
- OPC-UA Server – (Max 8 Clients)
- EDG – (Max 16 Exchanges)
- PROFINET – (Max 8 IO Devices)

USB Interface

- 1 USB-A 2.0

Memory Card

- Micro SD

Other Interface

- 1 RS-232

Environmental

- -40°C to 70°C

Distributor Switzerland



b+i automation ag
Rainweg 8
4710 Balsthal
Switzerland
+41 62 386 99 00
www.bi-automation.ch

United States Office

Emerson Automation Solutions
Intelligent Platforms, LLC
2500 Austin Dr
Charlottesville, VA

Germany Office

Emerson Automation Solutions
ICC Intelligent Platforms
GmbH
Memminger Straße 14
Augsburg, DE 86159

China Office:

Emerson Automation Solutions Intelligent
Platforms (Shanghai) Co., Ltd
No.1277, Xin Jin Qiao Rd, Pudong,
Shanghai, China, 201206

Brazil Office:

Emerson Automation Solutions
Rua Irmã Gabriela, 51 – Cidade Monções
São Paulo – SP, 04571-130

Singapore Office

Emerson Automation Solutions Intelligent
Platforms Asia Pacific Pte. Ltd.
1 Pandan Crescent,
Singapore, 128461

India Office

Emerson Automation Solutions
Intelligent Platforms Pvt. Ltd.,
Building No.8, Ground Floor Velankani Tech Park, No.43
Electronics City Phase I, Hosur Rd
Bangalore-560100

©2019 Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. [Brand name] is a mark of one of the Emerson Automation Solutions family of business units. All other marks are property of their respective owners.

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services describe herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products an any time without notice.